



# IH Risers

## FEATURES and SPECS

- Compatible with 1/2" IPS female threads and in use with teflon
- IH 3JTTFST BSF NBEF XJUI DVU MFOHIUT PE 17\$ 'MFYX)JUFUXP NBMF BEBQ UFSI
- The PVC Flex Hose is Ultra Violet Ray (UV) and Algae Resistant (AR).

The riser is offered in different color option variations: Black, Brown or Reclaimed Stripe.

- GPH also offers this product of preset lengths of 6", 8", 12", 18", 24", 36", 48", custom lengths are available.
  - GPH's IH Risers are designed to be used in low pressure Irrigation Systems no great than 50 psi. This PVC Flex Hose should never be used in Hot Water or High Pressure Applications.

## SPECS

- The subject non-rigid-poly-vinyl chloride (PVC) hose is to be extruded using GPH's integrally compounded algae-resistant S-0214 material.
- PVC Flex Hose must be non-rigid and leak free and in compliance with **ASTM D228 and ASTM D2122.**
- PVC Flex Hose must be in compliance with ASTM F-21-70\* Fungus Testing and ASTM G-42\* Algae Testing.
- The tubing must be smooth inside and out, free of foreign material contamination and have no cracks, pinholes, dents, wrinkles or blisters.

Size	Inside Dia. (in.)	Wall thickness (in.)	Outside Dia (in.)
1/2(HOSE)	0.5	0.09	0.68

