



- ① FINISH GRADE/TOP OF MULCH
- ② LARGE VALVE BOX WITH COVER:
- ③ REMOTE CONTROL VALVE
- ④ ID TAG
- ⑤ WATERPROOF CONNECTION:
- ⑥ 30-INCH LINEAR LENGTH OF WIRE, COILED
- ⑦ PROFLOW BASKET FILTER
- ⑧ SCH. 80 PVC UNION, TYPICAL
- ⑨ PRESSURE REGULATOR  
50 PSI
- ⑩ PVC SCH 40 MALE ADAPTER  
MIPT x SOCKET
- ⑪ LATERAL PIPE
- ⑫ PVC SCH 40 ELL
- ⑬ PVC SCH 80 NIPPLE (2-INCH  
LENGTH, HIDDEN) AND PVC  
SCH 40 ELL
- ⑭ PVC SCH 40 TEE OR ELL
- ⑮ RED BRICK SUPPORT
- ⑯ MAINLINE PIPE
- ⑰ 3-INCH MINIMUM DEPTH OF  
3/4-INCH WASHED GRAVEL
- ⑱ PVC SCH 80 NIPPLE
- ⑲ LANDSCAPE FABRIC, WRAP UP  
AND OVER BOX HOLES

**GPH**

MAX. FLOW  
3/4" - 22 GPM  
1" - 34 GPM

OPERATING RANGE  
0.1 TO 34.0 GPM

OPERATING PRESSURE  
15 UP TO 148 PSI

## ProFlow JarTop Basket Filter