

X-Flex Pressure Rated PVC Flex Hose - (Spa Hose)

Applications:

The Bio-based Flexible PVC Pressure Rated Hose is not only Eco-Friendly but Super Strong. We manufacture the X-Flex from phthalate-free flex PVC which provides for not only the toughest hose but also the most environmentally responsible. Our unique manufacturing process of adding an integral spiral rigid spine allows for flexibility while allowing for higher burst pressures than standard Flex PVC Irrigation Hose.

S0214 material that shall conform to all of the following:

Hardness (A Shore) - 92 to 86 tested per ASTM Method D2240 Specific Gravity, nominal - 1.42 +/- .02 tested per ASTM Method D792(A) 100% Modulus: -2900 (psi) Tensile Strength, minimum -2950 (psi) tested per ASTM Method D412 Brittleness Temp., maximum -20 C tested per ASTM Method D746(A) Elongation: -270%

Features:

- Multi Purpose** - High Pressure applications for Pool/Spa and Commercial Landscape.
- Variety** - Available in 6 different sizes: 1/2" Irr (3/8" IPS), 1/2" IPS, 3/4" IPS, 1" IPS, 1 1/2" IPS and 2" IPS.
- Offered in 2 colors:** Black or White
- Ease of Installation** - PVC Tubing is compatible with schedule 40 or 80 slip fittings of the corresponding size when solvent welded or "glued". We suggest using a P70 Primer and then IPS Weld-On part # 795 or 2795 (for flexible tubing), follow proper solvent welding techniques.



GPH Irrigation Products
 15372 Valencia Ave.
 Fontana, CA 92336
 866.582.9684

Website: gphirrigation.com



Part #	Size	Coil Length	Working Pressure	Burst Pressure
GXF050	Black, 1/2" Irrigation	50 ft	125 psi	370 psi
GXF050W	White, 1/2" Irrigation	50 ft	125 psi	370 psi
GXF075	Black, 3/4" IPS	50 ft	120 psi	355 psi
GXF075W	White, 3/4" IPS	50 ft	120 psi	355 psi
GXF100	Black, 1" IPS	50 ft	120 psi	355 psi
GXF100W	White, 1" IPS	50 ft	120 psi	355 psi
GXF150	Black, 1 1/2" IPS	50 ft	120 psi	355 psi
GXF150W	White, 1 1/2" IPS	50 ft	120 psi	355 psi
GXF200	Black, 2" IPS	50 ft	120 psi	355 psi
GFX200W	White, 2" IPS	50 ft	120 psi	355 psi