



GPCBA Series High Flow Bubbler's

FEATURES and SPECS

- Adjustable Flow Range: .25 - 2 GPM
- Maintains even flow at pressures between 20 and 70 PSI.
- Compatible with 1/2" MIPT Threads.
- Available in Black, Mulch and Desert Color.
- Bubbler's Manufactured from high impact ABS material.
- Water shall flow and bubble from the umbrella/cap of the bubbler, maintains a consistant water pattern.
- Self sealing screen eliminates need for teflon tape.

Check Valve Option

- Spec-Check's 10 psi Internal Spring, Check Valve Helps Prevent Drainage and Maintains Up to 15 Column Foot Of Water.
- Check Valve is installed inside of the filter.
- Check Valve devise works with Spring loaded stainless steel ball.

Product Overview

The High-Flow Adjustable Threaded Irrigation Bubbler is designed for landscapes requiring flexible, high-volume water delivery with precise control. Its universal threaded 1/2" IPS inlet thread that ensures secure installation into risers, manifolds, or micro-irrigation adapters. The adjustable flow mechanism transitions smoothly from soft drip to powerful bubbling output, supporting deep root penetration and healthy plant growth.

Flow can be fine-tuned with a Phillips screwdriver. Constructed from UV-stabilized materials, this bubbler provides long-lasting durability for trees, shrubs, and high-demand zones.

GPCB
w/ Check Valve
How to Order:
GPCBCV25D

Color:
- **D** (Desert Camo)
- **M** (Mulch Camo)
- **blank** (Black)

Flow:
- **25** (1/4 GPM)
- **50** (1/2 GPM)
- **1** (1 GPM)
- **A** (Adjustable)

